

KEY FEATURES

- Precision lightweight construction
- Optional heat exchanger mount kit
- Hand & feed to main axis
- Optional Auto Feed
- ER40 Collet spindle
- Optional ISO 30 spindle
- Can be mounted directly to Mirage gantries
- Available in pneumatic and hydraulic drive options

DESCRIPTION

The LMR 2000 is lighter than the MR range equivalent and has a maximum stroke of 2000mm (80").

APPLICATIONS

The LMR2000 range is designed primarily for use on heat exchangers, but is robust enough to be used for many other general in-situ milling applications.

LMR2000 SPECIFICATIONS

Max stroke (X main axis)	2015mm (80")
Down Feed Axis Stroke	95mm (3.74")
Max Cutter diameter ER40 Collet Spindle	25mm (0.984")
Max Cutter diameter Optional ISO Collet Spindle	80mm (3.15")
Hand Feed	5mm (0.197") per rev
HYDRAULIC DRIVE	
Auto Feed Rate Hydraulic (optional)	105mm (4.13") per min
Max Spindle RPM (Hydraulic)	630
Spindle Hydraulic Supply Required	50L/min (13.21 gal/min)
Auto Feed Hydraulic Supply Required	20L/min (5.28 Gal/min)
Hydraulic Milling Head Power	3.73kw (5hp)
PNEUMATIC DRIVE	
Auto Feed rate Pneumatic (optional)	26.5mm (1.04") per min
Max Spindle RPM (Pneumatic)	655
Spindle Pneumatic Supply Required	1800 L/min (63.6 cfm)
Auto Feed Pneumatic Supply Required	2000L/min (70.6cfm)
Pneumatic Milling Head Power	1.7kw (2.27hp)

INCLUDED AS STANDARD WITH MACHINE

The machine is supplied complete with the following items;

- ✓ All required mounting bolts
- ✓ Air filter lubricator and hose connection for pneumatic machines (when required)
- ✓ Storage / shipping box
- ✓ CE certificate
- ✓ Packing list and manual
- ✓ Milling Rail Hold Down Brackets
- ✓ Pneumatic Milling Head with ER40 Collet Spindle, or Hydraulic Milling Head with ER40 Collet Spindle

SET UP AND OPERATION

The operator must be:

- Trained and conversant with the product
- Able to identify the correct and incorrect use of static or portable machines.
- Comply with all local and internationally recognised regulations regarding safe use of powered machines.

MACHINE WEIGHT

LMR2000	168 kg	370 lbs
---------	--------	---------

SHIPPING WEIGHT

LMR2000	260 kg	573 lbs
---------	--------	---------

SHIPPING DIMENSIONS

	Length	Width	Height
LMR2000	269cm (106")	68cm (27")	60cm (24")

All weights and dimensions approximate and for guidance only.

IMPORTANT
PLEASE REVIEW OPTIONS, ACCESSORIES
AND SPARE PARTS ON NEXT PAGES



LMR MILLING MACHINE OPTIONS & ACCESSORIES

PP2 11 KW 3 Phase Power Pack

(For Hydraulic Machines Only) 60 L.P.M up to 90 BAR – proportional remote operation 24 volt dc fully CE marked.



Magnetic Mounts

Fast set mounting system featuring switch magnet mounts for the Mirage range of 2 and 3 axis milling machines and drilling and tapping machines.




LMR2000-2 Light Milling Head -

ISO 30 Spindle with Adjustable Gear Ratios. Hydraulic or Pneumatic versions available.



MR2000-3

Wedge Levelling Feet



LMR2000-4

Pneumatic LMR Auto Feed Kit

Or

LMR2000-8

Hydraulic LMR Auto Feed Kit



LMR2000-6

Heat Exchanger Mount Plates



LMR2000-11

End Mill & Collet Set ISO30



Gantry Mill Kit

Provides 3-Axis milling capability. See separate data sheet for further information

